



35/20

| Model | | | | | | | | |
|-------|-------|-------|-------|----------|------------|-------|-------|-----------|
| 75/80 | L/Min | Ltrs | Bar | Kw HP | Volts/Hz | dB(A) | KG | CM-hxwx d |
| | 78 | 9 | 8 | 0.50 0.5 | 220-240/50 | 55 | 33 | 41x54x34 |
| FAD | 1 Bar | 2 Bar | 3 Bar | 4 Bar | 5 Bar | 6 Bar | 7 Bar | 8 Bar |
| L/Min | 62 | 63 | 59 | 57 | 56 | 54 | 53 | 52 |

Max Duty Cycle = 50%. 110 volt available on request

Only Bambi offers this unique combination of piston rings and high performance pump* which means the MD range is perfect for critical applications; scientific laboratories, dentistry, pneumatic control systems and any other application requiring ultra clean, ultra silent air!

With sound levels from just 40dB(A) and almost no vibration when running, Bambi MD Compressors can be located in the work area without causing any noise intrusion. Perfect as a stand alone air centre or for a range of OEM requirements.

| Model | | | | | | | | |
|--------|-------|-------|-------|----------|------------|-------|-------|-----------|
| 75/150 | L/Min | Ltrs | Bar | Kw HP | Volts/Hz | dB(A) | KG | CM-hxwx d |
| | 78 | 15 | 8 | 0.50 0.5 | 220-240/50 | 55 | 37 | 67x46x30 |
| FAD | 1 Bar | 2 Bar | 3 Bar | 4 Bar | 5 Bar | 6 Bar | 7 Bar | 8 Bar |
| L/Min | 62 | 63 | 59 | 57 | 56 | 54 | 53 | 52 |

75/150v specification as above, Dimensions 54x37x37cm - 32KGs
Max Duty Cycle = 50%. 110 volt available on request

| Model | | | | | | | | |
|--------|-------|-------|-------|----------|------------|-------|-------|-----------|
| 75/250 | L/Min | Ltrs | Bar | Kw HP | Volts/Hz | dB(A) | KG | CM-hxwx d |
| | 78 | 24 | 8 | 0.50 0.5 | 220-240/50 | 55 | 35 | 59x63x24 |
| FAD | 1 Bar | 2 Bar | 3 Bar | 4 Bar | 5 Bar | 6 Bar | 7 Bar | 8 Bar |
| L/Min | 62 | 63 | 59 | 57 | 56 | 54 | 53 | 52 |

75/250v specification as above, Dimensions 57x41x43cm - 35KGs
Max Duty Cycle = 50%. 110 volt available on request



75/250v



75/250 with optional wheel kit

Ultra high performance with ultra low noise - the Bambi MD range. Designed for applications demanding the highest quality air supply with all the benefits of very low noise levels. At the heart of the range is the oil lubricated T75 pump unit developed to deliver 50% more air compared to other silent compressors and the *only* silent compressor fitted with piston rings eliminating oil carryover to the air supply.

| Model | | | | | | | | |
|-------|-------|-------|-------|----------|------------|-------|-------|-----------|
| 35/20 | L/Min | Ltrs | Bar | Kw HP | Volts/Hz | dB(A) | KG | CM-hxwx d |
| | 50 | 4 | 8 | 0.34 0.5 | 220-240/50 | 40 | 18 | 33x28x32 |
| FAD | 1 Bar | 2 Bar | 3 Bar | 4 Bar | 5 Bar | 6 Bar | 7 Bar | 8 Bar |
| L/Min | 45 | 40 | 37 | 35 | 34 | 33 | 32 | 31 |

Max Duty Cycle = 50%. 110 volt available on request



75/80



75/150



75/150v



75/250

| Model | | | | | | | | |
|---------|-------|-------|-------|---------|------------|-------|-------|-----------|
| 150/500 | L/Min | Ltrs | Bar | Kw HP | Volts/Hz | dB(A) | KG | CM-hxwx d |
| | 156 | 50 | 8 | 1.0 1.0 | 220-240/50 | 56 | 69 | 66x83x26 |
| FAD | 1 Bar | 2 Bar | 3 Bar | 4 Bar | 5 Bar | 6 Bar | 7 Bar | 8 Bar |
| L/Min | 124 | 126 | 118 | 114 | 112 | 108 | 106 | 104 |

Above dimensions exclude wheels, when fitted +4cm to height
Max Duty Cycle = 50%. 110 volt available on request



150/500 fitted with standard wheel kit supplied



150/500

The "V" designated models have the same specification as the horizontal versions but in an ultra compact package. All models have an 8 bar maximum working pressure, optional higher pressures are available on request.

As you would expect on this high quality, high performance range, the standard specification is very high; air receivers are internally powder coated to prevent corrosion*, internal valves are stainless steel and each model is equipped with a 10 micron air filter & outlet pressure regulator as standard. Models 150/500 & 225/1000 are supplied with easy to fit wheel kits, available as an option for 75/250.

| Model | | | | | | | | |
|----------|-------|-------|-------|---------|------------|-------|-------|-----------|
| 225/1000 | L/Min | Ltrs | Bar | Kw HP | Volts/Hz | dB(A) | KG | CM-hxwx d |
| | 234 | 100 | 8 | 1.5 1.5 | 220-240/50 | 57 | 108 | 72x118x35 |
| FAD | 1 Bar | 2 Bar | 3 Bar | 4 Bar | 5 Bar | 6 Bar | 7 Bar | 8 Bar |
| L/Min | 187 | 189 | 177 | 171 | 168 | 162 | 159 | 156 |

Above dimensions exclude wheels, when fitted +5cm to height
Max Duty Cycle = 50%. Requires 20 amp single phase power supply



225/1000



225/1000 fitted with standard wheel kit supplied



Unique Bambi Piston Rings



Internally Coated Receiver



High Output T75 Pump Unit



Low Noise Non Return Valve



10 Micron Outlet Filter & Adjustable Pressure Regulator

Bambi compressors have been designed to maximise efficiency and ensure years of trouble free operation, which together with our comprehensive warranty extending to 5 years on the air receiver explains why so many are in use worldwide in all types of vital applications.

*not model 35/20