

Enclosed - Regulated Speed (RS)

Motor Power (kW)	Model	Voltage/Phase		Starter Type	Mounting Config.	Maximum FAD m ³ /min (cfm)			Motor Speed (rpm)	Oil Capacity (litres)	Air Outlet (Rp)	Dimensions (mm)			Noise dB(A)	Weight (kg)	Air Quality (mg/m ³)
		50Hz	60Hz			6 bar	8 bar	10 bar				Depth	Width	Height			
11.0	HV11RS	400V 3Ph	460V 3Ph	v	Floor	1.74 (61.6)	1.56 (55.0)	1.37 (48.5)	870 to 1900	7.0	¾"	850	700	1550	69	393	<3
15.0	HV15RS					2.29(80.8)	2.03 (71.6)	1.72 (60.7)	870 to 1800						70	406	
18.0	HV18RS					2.96 (104.6)	2.75 (96.9)	2.51 (88.5)		7.5	1"				507		
22.0	HV22RS					3.53 (124.5)	3.22 (113.8)	3.07 (108.3)	870 to 1700	71	520						
30.0	HV30RS					5.38 (189.9)	4.87 (171.9)	4.51 (159.3)		23.0	73	909					
37.0	HV37RS					6.17 (217.8)	5.72 (202.1)	5.27 (186.1)	1115			900	1640	963			
45.0	HV45RS					7.47 (263.7)	6.90 (243.5)	6.51 (230.0)	992								